

| INPUT             |                                     |
|-------------------|-------------------------------------|
| Rated power       | 1500 VA                             |
| Voltage           | 220 / 230 / 240 V                   |
| Voltage tolerance | 230 V ( $\pm 25\%$ )                |
| Frequency         | 50 / 60 Hz with automatic selection |

| OUTPUT and INVERTER OUTPUT     |                             |
|--------------------------------|-----------------------------|
| Rated power                    | 1500 VA                     |
| Active power                   | 900 W                       |
| Wave form on battery           | Pseudo sinusoidal           |
| Frequency on battery operation | 50 or 60 Hz ( $\pm 0.5\%$ ) |

| BATTERIES             |                                      |
|-----------------------|--------------------------------------|
| Type                  | VRLA AGM maintenance-free lead based |
| Typical recharge time | 2-4 h                                |

| ENVIRONMENTAL         |   |
|-----------------------|---|
| Color                 | Black   |
| Communication         | USB + RS232   |
| Accessories provided  | 2 cables for powering loads; user manual  |
| Marks                 | CE  |
| Operating temperature | 0 °C - +40 °C   |
| Relative humidity     | 5-95% non-condensing  |
| Standards             | European directives: L V 2014/35/EU low voltage; EMC 2014/30/EU electromagnetic compatibility -- Directive and Standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; RoHS compliant |

| DATA               |                |
|--------------------|----------------|
| Weight             | 11.1 kg        |
| Dimensions (h w d) | 397x205x146 mm |